



SBGf Conference

18-20 NOV | Rio'25

Sustainable Geophysics at the Service of Society

In a world of energy diversification and social justice

Submission code: JP80LY9MP8

See this and other abstracts on our website: <https://home.sbgf.org.br/Pages/resumos.php>

Characterizing the high-frequency noise sources on a new seismological station in the southwestern region of São Paulo state

Caio Amaral (Inst. Astronomia Geofísica e C. Atmosféricas.; Inst. Pesquisas Tecnológicas do Estado de SP), Marcelo Bianchi (IAG - Universidade de São Paulo), Eriqui Inazaki (Fundação Florestal do Estado de São Paulo), Natália Henriques (Fundação Florestal do Estado de São Paulo)

Characterizing the high-frequency noise sources on a new seismological station in the southwestern region of São Paulo state

Copyright 2025, SBGf - Sociedade Brasileira de Geofísica/Society of Exploration Geophysicist. This paper was prepared for presentation during the 19th International Congress of the Brazilian Geophysical Society held in Rio de Janeiro, Brazil, 18-20 November 2025. Contents of this paper were reviewed by the Technical Committee of the 19th International Congress of the Brazilian Geophysical Society and do not necessarily represent any position of the SBGf, its officers or members. Electronic reproduction or storage of any part of this paper for commercial purposes without the written consent of the Brazilian Geophysical Society is prohibited.

Introduction

All seismological stations operating on Earth's surface have a characteristic seismic noise pattern. Usually, for frequencies below 1 Hz, the primary (2-10 s) and secondary microseism (10-20 s), along with the "hum" (65-500 s), are clearly visible at every station. Frequencies above 1 Hz are mainly composed of anthropogenic and environmental sources. The station Terra Rica/PR (TRCB), located in the northwestern region of Paraná state, was uninstalled due to the excessive presence of high-frequency noise. To replace TRCB, a new seismological station (MRDB) was installed at the Morro do Diabo State Park (Teodoro Sampaio/SP), located in the southwestern region of São Paulo state. The chosen location is situated approximately 7.0 km from the city of Teodoro Sampaio, 11.5 km from the main operational base of the preservation area, and 1.5 km from the nearest highway. Here, we present a first analysis of the characteristic high-frequency seismic noise of the station.

Method and/or Theory

To identify the dominant frequencies within the seismic signal recorded by the station, we calculated Probability Density Functions (PDFs) using continuous data to analyze the period-frequency spectrum. Analyzing the resulting PDFs allowed us to select a specific frequency window, and subsequently compute the Degree of Polarization (DoP) of the signal (Schimmel et al., 2003, 2004, 2011) to estimate the noise source direction. The DoP strategy was developed for characterizing microseismic noise (frequencies below 1 Hz), which is dominated by Rayleigh waves and assumes a pure retrograde particle motion (PRPM) in a vertical plane for wave propagation. However, in high-frequency noise it is harder to identify the PRPM correctly. To ensure that our analyzed signal consisted of PRPM signals only, we selected time windows with at least 90% DoP.

Results and Conclusions

Analyses of the PDFs revealed that both MRDB and TRCB exhibited high dB values for frequencies above 1 Hz (compared to other permanent stations). TRCB displayed a flatter pattern, ranging between -110 and -120 dB across the three channels, while the pattern for MRDB remained between -100 and -125 dB, with two small peaks at approximately 3 Hz and 10 Hz. For TRCB, we computed the DoP for the period between days 100 and 115 (julian, 2024). The results indicated peaks at frequencies near 2.6 Hz, 4 Hz, 7.4 Hz, and above 10 Hz. The most prominent noise sources were located south of the station (associated with identified farm infrastructure situated approximately 250m to the south), with a secondary source in the north direction (most likely the city of Terra Rica/PR, located about 8 km to the north). For MRDB, we computed the DoP for the same period, but for the year 2025. The results showed a frequency peak near 2.8 Hz and an increase of noise above 9 Hz. The 2.6 Hz peak was predominantly located in the southwest direction and is believed to be related to the nearby highway. The high values above 9 Hz were located in the northwest-southeast direction, with the most probable sources being the farms surrounding the park area and the city of Teodoro Sampaio/SP (located east of the station). In the southwest direction, corresponding to the park area, it was observed a reduced value of anthropogenic seismic noise. PDF hour analysis of noise sources indicate a reduction of the traffic in the highway, close to the MRDB station, between 23 and 6 hr everyday.